

**Tru Waste Retrieval Project
Richland WA
FF-01
Vapor Extraction System
(EU 1326; NOC 1039)**

Licensing File

Table of Contents

- 1) Licensing Checklist
- 2) Other Applicable Documentation (Emails, reports, calculations, etc.)
- 3) Informal Draft EU License
 - a) Licensee Comments on Informal Draft
 - b) Resolution of Comments
- 4) ~~Final License~~
2/28/09
- 5) *Final license*

1

LICENSING CHECKLIST

(Rev. 2)

Y to 1

Please initial boxes, as appropriate, rather than placing a check mark in the box

PREVIOUS EN 1326
NOC 804

RAES date received NA and IM# assigned LB 4751

NEW EN 1326
NOC 1089

Entered into RAES Tracking/RDIT 10-152. Completeness Review due Ad

To HP3 (responsible for facility) for assignment: JWS

To assigned HP2: Tom F

Add draft Table of Contents and separator pages to file.

Conduct completeness review using "Completeness Review Checklist" and draft "Completeness Notification" letter **within 20 days** of RAES date received. Discuss any concerns/issues with HP3 during this 20 day period.

Place "Completeness Review Checklist" in license file and prepare draft "Completeness Determination" letter. Letter *must go out within 30 days* of RAES date received.

- If application is incomplete, you may need to repeat this (and prior) step(s).
- If application complete, assign NOC ID and EU ID, as appropriate. **Do NOT** obsolete 'old' NOC, EU, etc. before the new final, approved, license is issued (you may have to exclude old from AOP for printing purposes).

Forward license file and draft "Completeness Determination" letter to HP3 for review. (If 28-day draft has already been reviewed by licensee and HP3 and is ready to go out at the 30 day mark, you may combine completeness and 28-day draft.)

HP3 - work with HP2 to resolve any comments then forward license file and draft "Completeness Determination" letter to HSC for review.

HSC - work with HP3 to resolve any comments then forward draft "Completeness Determination" letter to AA3 for finalization (HSC will update RAES Tracking/RDIT upon transmittal and will note the 28-Day Draft Due Date, below, upon returning file to you). You now have **60 days** to issue the official 28-Day Draft Approval letter.


28-Day Draft Due Date: _____ (See next step, immediately.)

Is it necessary to send the 20-Day City Notification? If yes, prepare **ASAP** and forward to HP3 for review (follow same process as above for letter issuance [HP3 -> HSC -> AA3]). HSC will update RAES Tracking/RDIT upon transmittal and will notify you of 20-Day Comment Due Date, below, upon returning the file to you).


- USDOE-RL Hanford Site is exempt from this requirement.
- If RAEL is part of a Materials or Waste license, the responsibility falls on them to notify the city.
- We issue these notifications for *new licenses or renewals only*; we do not issue them for modifications.


20-Day Comment Due Date: _____


(see page 2)


 Within 40 days _____ of completeness determined, complete thorough review of application and draft license. **Any EU specific conditions must have justification/basis documented in the 'explanation' section of the database.** Discuss any concerns/issues with HP3 during this 40 day period. Also, have HSC do an informal review of the license for consistency before sending to the licensee.

 HSC Informal License Review


 Send informal draft license to licensee for review, allowing them a **week to 10 days** to get comments back to you. *Be sure to include a 'due date'.*

 Upon receipt of response from licensee, resolve any comments/issues/concerns right away and finalize the draft license and transmittal letter (28-day Draft). **At least 3-5 days** before 28-Day Draft Due Date, send license file, draft transmittal letter, and draft license to HP3 for final review.

 HP3 approves and forwards license file and draft letter to HSC for review. HSC reviews and forwards to AA3 for finalization (HSC will hold file until licensee receives 28-day draft).


 Upon licensee receipt of 28-day draft, HSC will update RAES Tracking/RDIT, verify database concurrence, and return license file to HP2 with due date for licensee response or final issuance of license.

Final Due Date: 12/19/10


 Once licensee has accepted, or the 28 days has expired (**no more than 2-3 days before**), obtain an approval number (AIR#) from AA3 and prepare final license and "Final Approval" letter. Send license file (*be sure table of contents provides for final letter/license*), final transmittal letter, and final license to HP3 for final review.

 HP3 approves and forwards to HSC for review. HSC forwards to AA3 for finalization.


HSC finalizes:

 Add final letter(s)

 Update RAES Tracking/RDIT

 Verify database concurrence

 Update Licensee List

 Add final file to database 'inbox' to be entered/scanned

2

Frazier, Thomas (DOH)

From: Faust, Eric T <Eric.Faust@rl.doe.gov>
Sent: Tuesday, September 13, 2016 8:59 AM
To: Frazier, Thomas (DOH)
Cc: Schmidt, John W (DOH); Karschnia, Paul T; Carleo, Frank J; Engelmann, Richard H
Subject: RE: Informal Drafts of Transuranic Waste Retrieval Project Licenses NOCs 1035 to 1040
Attachments: NOC 1037 EU 1322, Transuranic Waste Portable Enclosure System #1 rl edits.pdf; NOC 1040 EU 1327 Transuranic Waste Next Generation Retrieval (active) rl edits.pdf

Tom,

Sorry for the wait. Please see attached NOCs for 1037 and 1040. We highlighted in yellow the instances where either NGR or PES should be removed from the licenses (instances of NGR should be redacted in NOC 1037 and instances of PES should be redacted in NOC 1040). Also in NOC 1040, we had questions regarding references to NOC 486. We indicated the comments in the yellow text bubble comment function in the pdf. These were the only comments that we have.

Thanks for the opportunity,

Eric
376-9607

From: Frazier, Thomas (DOH) [mailto:Thomas.Frazier@DOH.WA.GOV]
Sent: Tuesday, August 30, 2016 3:01 PM
To: Faust, Eric T <Eric.Faust@rl.doe.gov>; Karschnia, Paul T <Paul_T_Karschnia@rl.gov>
Cc: Schmidt, John <john.schmidt@doh.wa.gov>
Subject: Informal Drafts of Transuranic Waste Retrieval Project Licenses NOCs 1035 to 1040

Eric and Tad,

Here are informal drafts of the Licenses for the Transuranic Waste Project emission units for your review and comment.

Sincerely,

Tom
946-0774

3

Emission Unit ID: 1326

200W 296-P-53

Vapor Extraction System

This is a MINOR, ACTIVELY ventilated emission unit.

TRU Waste Retrieval

Emission Unit Information

Stack Height: ft. m. Stack Diameter ft. m.

Average Stack Effluent Temperature: degrees Fahrenheit. degrees Celsius.

Average Stack Exhaust Velocity: ft/second. m/second.

Abatement Technology ALARACT WAC 246-247-040(4)

state only enforceable: WAC 246-247-010(4), 040(5), 060(5)

Zone or Area	Abatement Technology	Required # of Units	Additional Description
	HEPA Filter		

Monitoring Requirements

state enforceable: WAC 246-247-040(5), 060(5), and federally enforceable: 40 CFR 61 subpart H

Federal and State Regulatory	Monitoring and Testing Requirements	Radionuclides Requiring Measurement	Sampling Frequency
WAC 246-247-075(3)	Near Field Monitoring	All radionuclides which could contribute greater than 0.1 mrem/yr to the MEI, or represent greater than 10% of the unabated PTE or represent greater than 25% of the abated dose.	once per month when operating. OK

Sampling Requirements Smears of the exhaust vent when the system is operated at any time within a month.

Additional Requirements

Additional monitoring or sampling requirements established by this License will be listed in the Conditions and Limitations section, if applicable.

Operational Status The VES will be used to remove volatile organic compounds from soil gases and vapors from vents located in 218-W-3A.

This Emission Unit has 1 active Notice(s) of Construction.

Project Title	Approval #	Date Approved	NOC_ID
Operation of the Transuranic Waste Retrieval Project (Replaces NOC 804)		Not Approved	1039

Conditions (state only enforceable: WAC 246-247-040(5), 060(5) if not specified)

- 1) The total abated emission limit for this Notice of Construction is limited to 1.00E-01 mrem/year to the Maximally Exposed Individual (WAC 246-247-040(5)).
- 2) This approval applies to those additional activities described below. No additional activities or variations on the approved activities that constitute a "modification" to the emission unit, as defined in WAC 246-247-030(16), may be conducted.

Transuranic waste retrieval involves the processes for removing and dispositioning buried suspect transuranic mixed low-level radioactive waste (hereafter called TRU waste) from Hanford Site burial trenches for storage or disposal at other approved locations. Dispositioning is the orderly administration and handling of waste (including contaminated soil) from the low level burial grounds to place it in approved storage or disposal status. The handling includes such actions as: packaging, labeling and tracking waste; venting, assaying, and staging waste; inspecting waste and waste staging areas; sampling/characterizing/designating waste; making arrangements for the transfer of waste; completing necessary paperwork; and performing radiological and/or industrial hygiene surveys.

The System that is associated with this approval is Vapor Extraction System

(VES)

See the following emission units for a detailed description of additional controls/conditions and limits under this approval:

- EU 455 HEPA Vacuums
- EU 486 200 Area Diffuse/ Fugitive; Operation of the Transuranic Waste Retrieval Project
- EU 755 Mobile Drum Venting System (Active Ventilation) (MDVS)
- EU 756 Mobile Drum Venting System (Passive Ventilation) (MDVS)
- EU 1181 Categorical Drum Venting System 2 (DVS2)
- EU 1322 Portable Enclosure System #1 (PES)
- EU 1326 Vapor Extraction System (VES) — *only?*
- EU 1327 Next Generation Retrieval (NGR)

3) The PTE for this project as determined under WAC 246-247-030(21)(a-e) [as specified in the application] is 3.92E+01 mrem/year. Approved are the associated potential release rates (Curies/year) of:

Am - 241 2.50E-03 Liquid/Particulate Solid
 Alpha release rate based on Am-241 + Progeny. It is recognized that other radionuclides may be present in very limited quantities.

Cs - 137 3.80E-02 Liquid/Particulate Solid
 Beta/Gamma release rate based on Cs-137 + Progeny. It is recognized that other radionuclides may be present in very limited quantities.

The radioactive isotopes identified for this emission unit are (no quantities specified):

- | | | | | |
|----------|----------|----------|----------|--------------|
| Am - 241 | Am - 243 | Cf - 252 | Cm - 244 | Cs - 134 |
| Cs - 137 | Eu - 152 | Eu - 154 | Pu - 238 | Pu - 239/240 |
| Pu - 241 | Sr - 90 | U - 234 | U - 235 | U - 236 |
| U - 238 | | | | |

The potential release rates described in this Condition were used to determine control technologies and monitoring requirements for this approval. DOE must notify the Department of a "modification" to the emission unit, as defined in WAC 246-247-030(16). DOE must notify the Department of any changes to a NESHAP major emission unit when a specific isotope is newly identified as contributing greater than 10% of the potential TEDE to the MEI, or greater than 25% of the TEDE to the MEI after controls. (WAC 246-247-110(9)) DOE must notify the Department of any changes to potential release rates as required by state or federal regulations including changes that would constitute a significant modification to the Air Operating Permit under WAC 173-401-725(4). Notice will be provided according to the particular regulation under which notification is required. If the applicable regulation(s) does not address manner and type of notification, DOE will provide the Department with advance written notice by letter or electronic mail but not solely by copies of documents.

4) RESTRICTION ON STARTUP

Prior to putting EU 1326, Vapor Extraction System, into service, USDOE will provide WDOH with the technical specifications for the fan and filter housings. WDOH will need to approve and reissue the License for Operation of the Transuranic Waste Retrieval Project prior to startup.

5) RELEASE RATES VES

It is assumed that there is a potential to have two degraded drums within the trench for the basis of the APQ, since only a portion of the trench is vented at any given time. Using a release fraction of 1E-03 for particulates, the predicted release rate (unabated) for the VES without any emissions control equipment is 4.0E 02 Ci/Yr. The predicted release rate (abated) with emissions control equipment is the same as unabated. The predicted release rates for the representative radionuclides Am-241+Progeny and Cs 137+Progeny are as follows:

Unabated PTE; Am-241+Progeny 2.5E-03 Ci/yr : Cs-137+Progeny 3.8E-02 Ci/yr
 Abated PTE; Am-241+Progeny 2.5E-03 Ci/y : Cs-137+Progeny 3.8E 02 Ci/yr
 (WAC 246-247-040(5) and WAC 246-247-060(5))

6) CONTROL TECHNOLOGY STANDARDS

The VES will contain HEPA-type filters but no credit is taken for them in the system. This system will rely on the near facility monitors, and since there is no monitoring system in the VES, the listed standards are not applicable.

7) CONTAMINATION CONTROL - confirmatory monitoring

Periodic confirmatory monitoring will consist of periodic field surveys of swipes/smears taken at the exhaust point

when the system is operated any time within a month, combined with the continuous monitoring provided by the 200 Area near facility ambient air monitoring network. (WAC 246-247-040(5) and WAC 246-247-060(5))

8) PROCESS DESCRIPTION: VAPOR EXTRACTION SYSTEM VES

This approval applies to these additional activities described below. No additional activities or variations on the approved activities that constitute a "modification" to the emission unit, as defined in WAC 246-247-030(16), may be conducted.

The VES will be used to remove volatile organic compounds (VOCs) from soil gases and vapors from vents located in 218-W-3A. A powered and filtered system will be attached to the VES risers and operated in batch mode. This process will consist of venting the vapor space and will not include venting during excavation or retrieval activities. The existing vent lines in the burial grounds will be connected to a powered ventilation system which will remove VOCs from the vapor space. The entire trench will not be vented as a unit, but the powered venting system will be positioned over a section of the trench and then moved further along, connecting to the nearest VES riser(s) as required per project direction.

Flexible hoses are connected from the vents to the VES. Vapor from the vents may be drawn through a demister and primary water separator (dropout tank) before it passes through a HEPA-type filter. The vapor stream leaving may then pass through a cooler before reaching the primary granular-activated carbon (GAC) canister. From the primary GAC canister the vapor line flows into the polishing GAC canister. The vapor stream leaving the polishing GAC canister is exhausted out of the VES stack. (WAC 246-247-040(5) and WAC 246-247-060(5))

9) ABATEMENT TECHNOLOGY: EXCAVATION AND RETRIEVAL OF CONTAINERS

It is recognized that other radionuclides may be present in very limited quantities. Encountering contamination is expected during excavation. The administrative control points set in this emission unit for contamination, as monitored by standard radiological field instrumentation, will be used to bound emissions based on current efficiencies of typical RadCon field contamination instruments.

The controls listed within this approval apply to TRU Waste Retrieval Project open air excavation and retrieval activities. (WAC 246-247-040(5) and WAC 246-247-060(5))

10) ABATEMENT TECHNOLOGY: VAPOR EXTRACTION SYSTEM VES

Operation of the Vapor Extraction System: A VES powered ventilation system operated for several years in the LLBG as a Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) activity associated with the Groundwater Project. No radionuclide particulate emissions were detected from the VES vents during this operation. However, based on engineering estimates and the operation of not venting the entire trench at once, but in a series of sections, it is assumed that the equivalent radionuclide contents of two degraded containers per vented section will provide the basis for the source of potential emissions. A HEPA type filter may be used, but no credit is taken for abatement. The annual average volumetric flow rate through this exhaust system is 4.7E-02 cubic meters/s. (WAC 246-247-040(5) and WAC 246-247-060(5))

Emission Unit ID: 1326

200W 296-P-53

Vapor Extraction System

This is a MINOR, ACTIVELY ventilated emission unit.

TRU Waste Retrieval

Emission Unit Information

Stack Height: ft. m. Stack Diameter ft. m.

Average Stack Effluent Temperature: degrees Fahrenheit. degrees Celsius.

Average Stack Exhaust Velocity: ft/second. m/second.

Abatement Technology ALARACT WAC 246-247-040(4)

state only enforceable: WAC 246-247-010(4), 040(5), 060(5)

Zone or Area	Abatement Technology	Required # of Units	Additional Description
	HEPA Filter		

Monitoring Requirements

state enforceable: WAC 246-247-040(5), 060(5), and federally enforceable: 40 CFR 61 subpart H

Federal and State Regulatory	Monitoring and Testing Requirements	Radionuclides Requiring Measurement	Sampling Frequency
WAC 246-247-075(3)	Near Field Monitoring	All radionuclides which could contribute greater than 0.1 mrem/yr to the MEI, or represent greater than 10% of the unabated PTE or represent greater than 25% of the abated dose.	Once per month when operating.

Sampling Requirements Smears of the exhaust vent when the system is operated at any time within a month.

Additional Requirements

Additional monitoring or sampling requirements established by this License will be listed in the Conditions and Limitations section, if applicable.

Operational Status The VES will be used to remove volatile organic compounds from soil gases and vapors from vents located in 218-W-3A

This Emission Unit has 1 active Notice(s) of Construction.

Project Title	Approval #	Date Approved	NOC_ID
Vapor Extraction System Operation (Replaces NOC 804)		Not Approved	1039

Conditions (state only enforceable: WAC 246-247-040(5), 060(5) if not specified)

- 1) The total abated emission limit for this Notice of Construction is limited to 1.50E-02 mrem/year to the Maximally Exposed Individual (WAC 246-247-040(5)).
- 2) This approval applies to those additional activities described below. No additional activities or variations on the approved activities that constitute a "modification" to the emission unit, as defined in WAC 246-247-030(16), may be conducted.

Transuranic waste retrieval involves the processes for removing and dispositioning buried suspect transuranic mixed low-level radioactive waste (hereafter called TRU waste) from Hanford Site burial trenches for storage or disposal at other approved locations. Dispositioning is the orderly administration and handling of waste (including contaminated soil) from the low level burial grounds to place it in approved storage or disposal status. The handling includes such actions as: packaging, labeling and tracking waste; venting, assaying, and staging waste; inspecting waste and waste staging areas; sampling/characterizing/designating waste; making arrangements for the transfer of waste; completing necessary paperwork; and performing radiological and/or industrial hygiene surveys.

See the following for a detailed description of specific controls/conditions for each EU associated with the

Transuranic Waste Retrieval Project:

~~EU 455 HEPA Vacuums~~

~~EU 486 200 Area Diffuse/Fugitive; Operation of the Transuranic Waste Retrieval Project~~

- EU 755 Mobile Drum Venting System (Active Ventilation) (MDVS)
- EU 756 Mobile Drum Venting System (Passive Ventilation) (MDVS)
- EU 1181 Categorical Drum Venting System 2 (DVS2)
- EU 1322 Portable Enclosure System #1 (PES)
- EU 1326 Vapor Extraction System (VES)
- EU 1327 Next Generation Retrieval (NGR)

3) The PTE for this project as determined under WAC 246-247-030(21)(a-e) [as specified in the application] is 1.50E-02 mrem/year. Approved are the associated potential release rates (Curies/year) of:

Am - 241 2.50E-03 Liquid/Particulate Solid

Alpha release rate based on Am-241 + Progeny. It is recognized that other radionuclides may be present in very limited quantities.

Cs - 137 3.80E-02 Liquid/Particulate Solid

Beta/Gamma release rate based on Cs-137 + Progeny. It is recognized that other radionuclides may be present in very limited quantities.

The radioactive isotopes identified for this emission unit are (no quantities specified):

- | | | | | |
|----------|----------|----------|----------|--------------|
| Am - 241 | Am - 243 | Cf - 252 | Cm - 244 | Cs - 134 |
| Cs - 137 | Eu - 152 | Eu - 154 | Pu - 238 | Pu - 239/240 |
| Pu - 241 | Sr - 90 | U - 234 | U - 235 | U - 236 |
| U - 238 | | | | |

The potential release rates described in this Condition were used to determine control technologies and monitoring requirements for this approval. DOE must notify the Department of a "modification" to the emission unit, as defined in WAC 246-247-030(16). DOE must notify the Department of any changes to a NESHAP major emission unit when a specific isotope is newly identified as contributing greater than 10% of the potential TEDE to the MEI, or greater than 25% of the TEDE to the MEI after controls. (WAC 246-247-110(9)) DOE must notify the Department of any changes to potential release rates as required by state or federal regulations including changes that would constitute a significant modification to the Air Operating Permit under WAC 173-401-725(4). Notice will be provided according to the particular regulation under which notification is required. If the applicable regulation(s) does not address manner and type of notification, DOE will provide the Department with advance written notice by letter or electronic mail but not solely by copies of documents.

4) RESTRICTION ON STARTUP

Prior to putting EU 1326, Vapor Extraction System into service, USDOE will provide WDOH with the technical specifications for the fan and filter housings. WDOH will need to approve and reissue the License for Operation of the Transuranic Waste Retrieval Project prior to startup.

5) RELEASE RATES - VES

It is assumed that there is a potential to have two degraded drums within the trench for the basis of the APQ, since only a portion of the trench is vented at any given time. Using a release fraction of 1E-03 for particulates, the predicted release rate (unabated) for the VES without any emissions control equipment is 4.0E 02 Ci/Yr. The predicted release rate (abated) with emissions control equipment is the same as unabated. The predicted release rates for the representative radionuclides Am-241+Progeny and Cs 137+Progeny are as follows:

Unabated PTE;	Am-241+Progeny	2.5E-03 Ci/yr	:	Cs-137+Progeny	3.8E-02 Ci/yr
Abated PTE;	Am-241+Progeny	2.5E-03 Ci/y	:	Cs-137+Progeny	3.8E 02 Ci/yr

(WAC 246-247-040(5) and WAC 246-247-060(5))

6) CONTROL TECHNOLOGY STANDARDS

The VES will contain HEPA-type filters, but no credit is taken for them in the system. This system will rely on the near facility monitors and, since there is no monitoring system in the VES, the listed standards are not applicable.

7) CONTAMINATION CONTROL - Confirmatory Monitoring

Periodic confirmatory monitoring will consist of periodic field surveys of swipes/smears taken at the exhaust point

when the system is operated any time within a month, combined with the continuous monitoring provided by the 200 Area near facility ambient air monitoring network. (WAC 246-247-040(5) and WAC 246-247-060(5))

8) **PROCESS DESCRIPTION - VES**

This approval applies to these additional activities described below. No additional activities or variations on the approved activities that constitute a "modification" to the emission unit, as defined in WAC 246-247-030(16), may be conducted.

The VES will be used to remove volatile organic compounds (VOCs) from soil gases and vapors from vents located in 218-W-3A. A powered and filtered system will be attached to the VES risers and operated in batch mode. This process will consist of venting the vapor space and will not include venting during excavation or retrieval activities. The existing vent lines in the burial grounds will be connected to a powered ventilation system which will remove VOCs from the vapor space. The entire trench will not be vented as a unit, but the powered venting system will be positioned over a section of the trench and then moved further along, connecting to the nearest VES riser(s) as required per project direction.

Flexible hoses are connected from the vents to the VES. Vapor from the vents may be drawn through a demister and primary water separator (dropout tank) before it passes through a HEPA-type filter. The vapor stream leaving may then pass through a cooler before reaching the primary granular-activated carbon (GAC) canister. From the primary GAC canister the vapor line flows into the polishing GAC canister. The vapor stream leaving the polishing GAC canister is exhausted out of the VES stack. (WAC 246-247-040(5) and WAC 246-247-060(5))

9) **ABATEMENT TECHNOLOGY - Excavation and Retrieval of Containers**

It is recognized that other radionuclides may be present in very limited quantities. Encountering contamination is expected during excavation. The administrative control points set in this emission unit for contamination, as monitored by standard radiological field instrumentation, will be used to bound emissions based on current efficiencies of typical RadCon field contamination instruments.

The controls listed within this approval apply to TRU Waste Retrieval Project open air excavation and retrieval activities. (WAC 246-247-040(5) and WAC 246-247-060(5))

10) **ABATEMENT TECHNOLOGY - VES**

Operation of the Vapor Extraction System: A VES powered ventilation system operated for several years in the LLBG as a Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) activity associated with the Groundwater Project. No radionuclide particulate emissions were detected from the VES vents during this operation. However, based on engineering estimates and the operation of not venting the entire trench at once, but in a series of sections, it is assumed that the equivalent radionuclide contents of two degraded containers per vented section will provide the basis for the source of potential emissions. A HEPA type filter may be used, but no credit is taken for abatement. The annual average volumetric flow rate through this exhaust system is 4.7E-02 cubic meters/s. (WAC 246-247-040(5) and WAC 246-247-060(5))

4

LB# 4874

DUPLICATE



**AIR 16-1108
NOC 1039**

**STATE OF WASHINGTON
DEPARTMENT OF HEALTH**

**OFFICE OF RADIATION PROTECTION
309 Bradley Blvd., Suite 201 • Richland, Washington 99352
TDD Relay Service: 1-800-833-6388**

November 17, 2016

CERTIFIED MAIL

7015 0640 0007 5050 7814

Mr. Doug Shoop, Manager
United States Department of Energy
Richland Operations Office
P.O. Box 550, MSIN: A5-14
Richland, Washington 99352

Re: 28-Day Draft Approval of Notice of Construction (NOC) 1039

Reference: Email (LB# 4751), from John Schmidt (WDOH) to Multiple USDOE Staff, "NOC Consolidation", dated June 30, 2016.

Mr. Shoop:

As per the reference email, we have worked with your staff to make changes to move the NOCs and/or Emission Units (EUs) associated with this license from a one-to-many, to a one-to-one relationship. We appreciate your cooperation and willingness to support our future database needs and to make license actions more efficient and cost effective moving forward.

Pursuant to Chapter 246-247 of the Washington Administrative Code (WAC), the update will be approved according to the enclosed License for:

**Vapor Extraction System Operation (Replaces NOC 804)
(EU 1326; NOC 1039)**

The Washington State Department of Health (DOH) considers the conditions, controls, monitoring requirements, and limitations of the License integral to approval of your application.

This approval shall take effect, and a final approval letter issued, twenty-eight (28) days after you receive this letter, unless you apply for an adjudicative proceeding, as described below.

If you accept the conditions and limitations of this approval and do not wish to apply for an adjudicative proceeding, but wish to proceed under this approval before the 28 days have



Mr. Doug Shoop
November 17, 2016
Page 2 of 3

AIR 16-1108

elapsed, please notify us in writing and the DOH will issue a final approval letter. Your notice should be mailed or faxed to:

DOH - Office of Radiation Protection
Radioactive Air Emissions Section
309 Bradley Blvd., Suite 201
Richland, Washington 98352
FAX: (509) 946-0876


If there are concerns with the conditions and limitations of the approval, please notify the DOH. If attempts to resolve the concerns fail, the DOH will deny your application and you may contest the conditions and limitations of this approval, within 28 days of receipt, by filing the enclosed Request for Adjudicative Proceeding or a document providing substantially the same information with the DOH, Adjudicative Service Unit (ASU), in a manner that shows proof of service on the ASU. The ASU's address is:

DOH - Adjudicative Service Unit
310 Israel Road SE
P.O. Box 47879
Olympia, Washington 98504-7879

You must include a copy of this approval with your application. FILING SHALL NOT BE DEEMED COMPLETE UNTIL THE ADJUDICATIVE SERVICE UNIT ACTUALLY RECEIVES YOUR APPLICATION.

If you have any questions regarding this approval, please contact Mr. Thomas Frazier at thomas.frazier@doh.wa.gov or, by phone, at (509) 946-0774.

Sincerely,



P. John Martell, Manager
Radioactive Air Emissions Section

Enclosures: 1. Conditions and Limitations for EU 1326 (NOC 1039)
2. Request for Adjudicative Proceedings

cc: (see next page)

Mr. Doug Shoop
November 17, 2016
Page 3 of 3

AIR 16-1108

cc: Ruth Allen, WRPS
Matthew Barnett, PNNL
Lilyann Bauder, Ecology
Shawna Berven, WDOH
Lucinda Borneman, WRPS
Lee Bostic, BNI
Frank Carleo, CHPRC
Cliff Clark, USDOE-RL
Jack Donnelly, WRPS
Dennis Faulk, EPA
Eric Faust, USDOE-RL
Tom Frazier, WDOH
Gary Fritz, MSA
Philip Gent, Ecology
Daniel Heuston, Ecology
Reed Kaldor, MSA
Paul Karschnia, CHPRC
Ed MacAlister, USDOE-RL
Jim McAuley, EPA
Valarie Peery, Ecology
John Schmidt, WDOH
Jeff Voogd, WRPS
Davis Zhen, EPA
Environmental Portal
RAES Tracking: Line 16-152; EU 1326; NOC 1039

Emission Unit ID: 1326

200W 296-P-53

Vapor Extraction System

This is a MINOR, ACTIVELY ventilated emission unit.

TRU Waste Retrieval

Emission Unit Information

Stack Height: ft. m. Stack Diameter ft. m.

Average Stack Effluent Temperature: degrees Fahrenheit. degrees Celsius.

Average Stack Exhaust Velocity: ft/second. m/second.

Abatement Technology ALARACT WAC 246-247-040(4)

state only enforceable: WAC 246-247-010(4), 040(5), 060(5)

Zone or Area	Abatement Technology	Required # of Units	Additional Description
	HEPA Filter		

Monitoring Requirements

state enforceable: WAC 246-247-040(5), 060(5), and federally enforceable: 40 CFR 61 subpart H

Federal and State Regulatory	Monitoring and Testing Requirements	Radionuclides Requiring Measurement	Sampling Frequency
WAC 246-247-075(3)	Near Field Monitoring	All radionuclides which could contribute greater than 0.1 mrem/yr to the MEL, or represent greater than 10% of the unabated PTE or represent greater than 25% of the abated dose.	Once per month when operating.

Sampling Requirements: Smears of the exhaust vent when the system is operated at any time within a month.

Additional Requirements

Additional monitoring or sampling requirements established by this License will be listed in the Conditions and Limitations section, if applicable.

Operational Status The VES will be used to remove volatile organic compounds from soil gases and vapors from vents located in 218-W-3A

This Emission Unit has 1 active Notice(s) of Construction.

Project Title	Approval #	Date Approved	NOC_ID
Vapor Extraction System Operation (Replaces NOC 804)		Not Approved	1039

Conditions (state only enforceable: WAC 246-247-040(5), 060(5) if not specified)

- 1) The total abated emission limit for this Notice of Construction is limited to 1.50E-02 mrem/year to the Maximally Exposed Individual (WAC 246-247-040(5)).
- 2) This approval applies to those additional activities described below. No additional activities or variations on the approved activities that constitute a "modification" to the emission unit, as defined in WAC 246-247-030(16), may be conducted.

Transuranic waste retrieval involves the processes for removing and positioning buried suspect transuranic mixed low-level radioactive waste (hereafter called TRU waste) from Hanford Site burial trenches for storage or disposal at other approved locations. Positioning is the orderly administration and handling of waste (including contaminated soil) from the low level burial grounds to place it in approved storage or disposal status. The handling includes such actions as: packaging, labeling and tracking waste; venting, assaying, and staging waste; inspecting waste and waste staging areas; sampling/characterizing/designating waste; making arrangements for the transfer of waste; completing necessary paperwork; and performing radiological and/or industrial hygiene surveys.

See the following for a detailed description of specific controls/conditions for each EU associated with the

Transuranic Waste Retrieval Project:

- EU 455 Hanford Sitewide W-PORTEX 007
- EU 1440 200 Area Diffuse/ Fugitive; Operation of the Transuranic Waste Retrieval Project
- EU 755 Mobile Drum Venting System (Active Ventilation) (MDVS)
- EU 756 Mobile Drum Venting System (Passive Ventilation) (MDVS)
- EU 1181 Categorical Drum Venting System 2 (DVS2)
- EU 1322 Portable Enclosure System #1 (PES)
- EU 1326 Vapor Extraction System (VES)
- EU 1327 Next Generation Retrieval (NGR)

3) The PTE for this project as determined under WAC 246-247-030(21)(a-e) [as specified in the application] is 1.50E-02 mrem/year. Approved are the associated potential release rates (Curies/year) of:

Am - 241 2.50E-03 Liquid/Particulate Solid
 Alpha release rate based on Am-241 + Progeny. It is recognized that other radionuclides may be present in very limited quantities.

Cs - 137 3.80E-02 Liquid/Particulate Solid
 Beta/Gamma release rate based on Cs-137 + Progeny. It is recognized that other radionuclides may be present in very limited quantities.

The radioactive isotopes identified for this emission unit are (no quantities specified):

- | | | | | |
|----------|----------|----------|----------|--------------|
| Am - 241 | Am - 243 | Cf - 252 | Cm - 244 | Cs - 134 |
| Cs - 137 | Eu - 152 | Eu - 154 | Pu - 238 | Pu - 239/240 |
| Pu - 241 | Sr - 90 | U - 234 | U - 235 | U - 236 |
- U - 238

The potential release rates described in this Condition were used to determine control technologies and monitoring requirements for this approval. DOE must notify the Department of a "modification" to the emission unit, as defined in WAC 246-247-030(16). DOE must notify the Department of any changes to a NESHAP major emission unit when a specific isotope is newly identified as contributing greater than 10% of the potential TEDE to the MEL, or greater than 25% of the TEDE to the MEL after controls. (WAC 246-247-110(9)) DOE must notify the Department of any changes to potential release rates as required by state or federal regulations including changes that would constitute a significant modification to the Air Operating Permit under WAC 173-401-725(4). Notice will be provided according to the particular regulation under which notification is required. If the applicable regulation(s) does not address manner and type of notification, DOE will provide the Department with advance written notice by letter or electronic mail but not solely by copies of documents.

4) RESTRICTION ON STARTUP

Prior to putting EU 1326, Vapor Extraction System into service, USDOE will provide WDOH with the technical specifications for the fan and filter housings. WDOH will need to approve and reissue the License for Operation of the Transuranic Waste Retrieval Project prior to startup.

5) RELEASE RATES - VES

It is assumed that there is a potential to have two degraded drums within the trench for the basis of the APQ, since only a portion of the trench is vented at any given time. Using a release fraction of 1E-03 for particulates, the predicted release rate (unabated) for the VES without any emissions control equipment is 4.0E 02 Ci/Yr. The predicted release rate (abated) with emissions control equipment is the same as unabated. The predicted release rates for the representative radionuclides Am-241+Progeny and Cs 137+Progeny are as follows:

Unabated PTE;	Am-241+Progeny	2.5E-03 Ci/yr	:	Cs-137+Progeny	3.8E-02 Ci/yr
Abated PTE;	Am-241+Progeny	2.5E-03 Ci/y	:	Cs-137+Progeny	3.8E 02 Ci/yr

(WAC 246-247-040(5) and WAC 246-247-060(5))

6) CONTROL TECHNOLOGY STANDARDS

The VES will contain HEPA-type filters, but no credit is taken for them in the system. This system will rely on the near facility monitors and, since there is no monitoring system in the VES, the listed standards are not applicable.

7) CONTAMINATION CONTROL - Confirmatory Monitoring

Periodic confirmatory monitoring will consist of periodic field surveys of swipes/smears taken at the exhaust point

when the system is operated any time within a month, combined with the continuous monitoring provided by the 200 Area near facility ambient air monitoring network. (WAC 246-247-040(5) and WAC 246-247-060(5))

8) **PROCESS DESCRIPTION - VES**

This approval applies to these additional activities described below. No additional activities or variations on the approved activities that constitute a "modification" to the emission unit, as defined in WAC 246-247-030(16), may be conducted.

The VES will be used to remove volatile organic compounds (VOCs) from soil gases and vapors from vents located in 218-W-3A. A powered and filtered system will be attached to the VES risers and operated in batch mode. This process will consist of venting the vapor space and will not include venting during excavation or retrieval activities. The existing vent lines in the burial grounds will be connected to a powered ventilation system which will remove VOCs from the vapor space. The entire trench will not be vented as a unit, but the powered venting system will be positioned over a section of the trench and then moved further along, connecting to the nearest VES riser(s) as required per project direction.

Flexible hoses are connected from the vents to the VES. Vapor from the vents may be drawn through a demister and primary water separator (dropout tank) before it passes through a HEPA-type filter. The vapor stream leaving may then pass through a cooler before reaching the primary granular-activated carbon (GAC) canister. From the primary GAC canister the vapor line flows into the polishing GAC canister. The vapor stream leaving the polishing GAC canister is exhausted out of the VES stack. (WAC 246-247-040(5) and WAC 246-247-060(5))

9) **ABATEMENT TECHNOLOGY - Excavation and Retrieval of Containers**

It is recognized that other radionuclides may be present in very limited quantities. Encountering contamination is expected during excavation. The administrative control points set in this emission unit for contamination, as monitored by standard radiological field instrumentation, will be used to bound emissions based on current efficiencies of typical RadCon field contamination instruments.

The controls listed within this approval apply to TRU Waste Retrieval Project open air excavation and retrieval activities. (WAC 246-247-040(5) and WAC 246-247-060(5))

10) **ABATEMENT TECHNOLOGY - VES**

Operation of the Vapor Extraction System: A VES powered ventilation system operated for several years in the LLBG as a Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) activity associated with the Groundwater Project. No radionuclide particulate emissions were detected from the VES vents during this operation. However, based on engineering estimates and the operation of not venting the entire trench at once, but in a series of sections, it is assumed that the equivalent radionuclide contents of two degraded containers per vented section will provide the basis for the source of potential emissions. A HEPA type filter may be used, but no credit is taken for abatement. The annual average volumetric flow rate through this exhaust system is 4.7E-02 cubic meters/s. (WAC 246-247-040(5) and WAC 246-247-060(5))

**STATE OF WASHINGTON
DEPARTMENT OF HEALTH
ENVIRONMENTAL HEALTH PROGRAMS
OFFICE OF RADIATION PROTECTION**

In Re The Approval of:
**28-DAY DRAFT APPROVAL OF NOTICE
OF CONSTRUCTION (NOC) 1039**

Docket No:
REQUEST FOR ADJUDICATIVE PROCEEDING

Approval No: **AIR 16-1108**

THE STATE OF WASHINGTON TO:

**Mr. Doug Shoop, Manager
United States Department of Energy
Richland Operations Office
P.O. Box 550, MSIN: A5-14
Richland, Washington 99352**

If you wish to request an adjudicative proceeding, you or your attorney must COMPLETE AND FILE THIS FORM OR A DOCUMENT PROVIDING SUBSTANTIALLY THE SAME INFORMATION WITH THE DEPARTMENT OF HEALTH ADJUDICATIVE SERVICE UNIT WITHIN TWENTY-EIGHT (28) DAYS OF YOUR RECEIPT of this Request for Adjudicative Proceeding form and a copy of the Office of Radiation Protection's approval, AIR 16-1108.

You must file your application in a manner that shows proof of service on the Adjudicative Service Unit, at the following address:

Department of Health
Adjudicative Service Unit
310 Israel Road S.E.
P.O. Box 47879
Olympia, WA 98504-7879

With your application, you must include a copy of the Office of Radiation Protection's approval.

FILING SHALL NOT BE DEEMED COMPLETE UNTIL THE ADJUDICATIVE SERVICE UNIT ACTUALLY RECEIVES YOUR APPLICATION.

YOU HAVE THE RIGHT TO a formal hearing in this matter conducted pursuant to Revised Code of Washington (RCW) 43.70.115, Chapter 34.05 RCW, and Chapter 246-10 of the Washington Administrative Code (WAC). Alternatively, you may waive the formal hearing and submit a written statement and supporting documents setting out your position, your defenses, and any mitigating circumstances that you wish to bring to the Department's attention.

You have the right to be represented by an attorney at your own expense.

L

I WILL BE represented by an attorney. His/her name, address, and phone number are:

Name:

Address:

Phone:

I WILL NOT BE represented by an attorney.

If after submitting this request, you obtain attorney representation or change attorneys, you must notify the Adjudicative Service Unit.

II.

I DO NOT waive my right to a formal hearing.

I DO waive my right to a formal hearing. I understand that if I waive my right to a formal hearing, the Department may decide this matter solely with reference to information in the Department's possession and to such written statements and supporting documents as I may have submitted.

If you choose to waive your right to a formal hearing, please complete the following:

I AM NOT submitting documents to the Department in support of my position.

I AM submitting a sworn statement and/or other documents to the Department in support of my position. Instructions - Please indicate your responses below:

If you are submitting documents to the Department, please list and briefly identify all such documents in the space provided below and on any additional sheet that may be necessary.

III.

ADMISSION/DENIAL OF CONDITIONS OR LIMITATIONS

The Office of Radiation Protection's approval AIR 16-1108, dated November 17, 2016, contains conditions and limitations set out as numbered paragraphs. In the space below you must indicate, in good faith, whether you admit, or do not contest, or deny the conditions or limitations. Conditions or limitations denied or not contested may later be admitted. Conditions or limitations admitted or not contested shall be conclusively deemed true for further proceedings.

Instructions: I admit, deny, or do not contest the conditions or limitations as follows
(fill in the appropriate paragraph number):

	<u>Admit</u>	<u>Deny</u>	<u>Do Not Contest</u>
Paragraph ____	[]	[]	[]
Paragraph ____	[]	[]	[]
Paragraph ____	[]	[]	[]
Paragraph ____	[]	[]	[]
Paragraph ____	[]	[]	[]
Paragraph ____	[]	[]	[]
Paragraph ____	[]	[]	[]
Paragraph ____	[]	[]	[]
Paragraph ____	[]	[]	[]

Please attach any additional sheets that may be necessary to respond to all allegations.

If you have chosen not to waive your rights to a formal hearing, please state all grounds for contesting this matter in the space provided below and on any additional sheets that may be necessary.

IV.

You have the right to an interpreter, appointed at no cost, if you are a hearing impaired person or limited English speaking person. If any witness for you is a hearing impaired person or a limited English speaking person, an interpreter will be appointed at your expense.

I [DO] / [DO NOT] (circle one) request an interpreter be appointed. If an interpreter is requested, please indicate the person or persons for whom an interpreter is required and their primary language, and/or whether they are hearing impaired.

IF YOU FAIL TO FILE YOUR APPLICATION IN A TIMELY MANNER, OR IF YOU FILE YOUR APPLICATION TIMELY BUT FAIL TO APPEAR AT ANY SCHEDULED SETTLEMENT CONFERENCE, PREHEARING CONFERENCE, OR HEARING WITHOUT LEAVE TO DO SO, THE DEPARTMENT MAY DECIDE THIS MATTER WITHOUT YOUR PARTICIPATION AND WITHOUT FURTHER NOTICE TO YOU.

DATED this _____ day of _____, _____

Party

Party's Representative (if any)

WSBA #: _____

U.S. Postal Service
CERTIFIED MAIL® RECEIPT
 Domestic Mail Only

7015 0640 0007 5050 7814

For delivery information, visit our website at www.usps.com

OFFICIAL USE

Certified Mail Fee
 \$ 3.30

Extra Services & Fees (check box, add fee as appropriate)

Return Receipt (hardcopy) \$ 2.70

Return Receipt (electronic) \$ _____

Certified Mail Restricted Delivery \$ _____

Adult Signature Required \$ _____

Adult Signature Restricted Delivery \$ _____

Postmark
 Here

16-1108

Postage
 \$ 2.02

Total Postage and Fees
 \$ 8.62

Sent To

 Street and Apt. No., or PO Box No.

 City, State, ZIP+4®

PS Form 3800, April 2015 PSN 7530-02-000-9047 See Reverse for Instructions

SENDER: COMPLETE THIS SECTION

- Complete items 1, 2, and 3.
- Print your name and address on the reverse so that we can return the card to you.
- Attach this card to the back of the mailpiece, or on the front if space permits.

1. Article Addressed to:

Mr. Doug Shoop, Manager
 United States Department of Energy
 Richland Operations Office
 P.O. Box 550, MSIN: A5-14
 Richland, WA 99352



9590 9402 1337 5285 0588 65

2. Article Number (Transfer from service label)


7015 0640 0007 5050 7814

COMPLETE THIS SECTION ON DELIVERY

A. Signature
[Signature] Agent Addressee

B. Received by (Printed Name) DA Adams C. Date of Delivery 11/21/16

D. Is delivery address different from item 1? Yes No
 If YES, enter delivery address below



3. Service Type
- Adult Signature
 - Adult Signature Restricted Delivery
 - Certified Mail®
 - Certified Mail Restricted Delivery
 - Collect on Delivery
 - Collect on Delivery Restricted Delivery
 - Insured Mail
 - Insured Mail Restricted Delivery (over \$500)
 - Priority Mail Express®
 - Registered Mail™
 - Registered Mail Restricted Delivery
 - Return Receipt for Merchandise
 - Signature Confirmation™
 - Signature Confirmation Restricted Delivery

5



LB
4910

AIR 16-1224
NOC 1039

STATE OF WASHINGTON
DEPARTMENT OF HEALTH
OFFICE OF RADIATION PROTECTION
309 Bradley Blvd., Suite 201 • Richland, Washington 99352
TDD Relay Service: 1-800-833-6388

December 23, 2016

Mr. Doug Shoop, Manager
United States Department of Energy
Richland Operations Office
P.O. Box 550, MSIN: A5-14
Richland, Washington 99352

Re: Final Approval of Notice of Construction (NOC) 1039

Mr. Shoop:

Pursuant to Chapter 246-247 of the Washington Administrative Code (WAC), your modification was approved on December 19, 2016, according to the enclosed emission unit (EU) specific license for:

**Vapor Extraction System Operation (Replaces NOC 804)
(NOC 1039, EU 1326)**

The conditions, controls, monitoring requirements, and limitations of this license must be observed in order for you to be in compliance with WAC 246-247. Failure to meet any provision of this license may result in the revocation of approval, the issuance of Notices of Violation, or other enforcement actions under WAC 246-247-100.

If you have any questions regarding this approval, please contact Tom Frazier at Thomas.Frazier@doh.wa.gov or, by phone, at (509) 946-0774.

Sincerely,

John Martell, Manager
Radioactive Air Emissions Section

Enclosure: NOC 1039 for EU 1326

cc: (see next page)



Mr. Doug Shoop
December 23, 2016
Page 2 of 2

AIR 16-1224

cc: Ruth Allen, WRPS
Matthew Barnett, PNNL
Lilyann Bauder, Ecology
Shawna Berven, WDOH
Lucinda Borneman, WRPS
Lee Bostic, BNI
Frank Carleo, CHPRC
Cliff Clark, USDOE-RL
Jack Donnelly, WRPS
Rick Engelmann, CHPRC
Dennis Fäulk, EPA
Thomas Frazier, WDOH
Eric Faust, USDOE-RL
Gary Fritz, MSA
Philip Gent, Ecology
Reed Kaldor, MSA
Paul Karschnia, CHPRC
Jim McAuley, EPA
John Schmidt, WDOH
Jeff Voogd, WRPS
Environmental Portal
RAES Tracking: Line 16-152; EU 1326; NOC 1039

Emission Unit ID: 1326

200W 296-P-53

Vapor Extraction System

This is a MINOR, ACTIVELY ventilated emission unit.

TRU Waste Retrieval

Emission Unit Information

Stack Height: ft. m. Stack Diameter ft. m.

Average Stack Effluent Temperature: degrees Fahrenheit. degrees Celsius.

Average Stack Exhaust Velocity: ft/second. m/second.

Abatement Technology ALARACT WAC 246-247-040(4)

state only enforceable: WAC 246-247-010(4), 040(5), 060(5)

Zone or Area	Abatement Technology	Required # of Units	Additional Description
	HEPA Filter		

Monitoring Requirements

state enforceable: WAC 246-247-040(5), 060(5), and federally enforceable: 40 CFR 61 subpart H

Federal and State Regulatory	Monitoring and Testing Requirements	Radionuclides Requiring Measurement	Sampling Frequency
WAC 246-247-075(3)	Near Field Monitoring	All radionuclides which could contribute greater than 0.1 mrem/yr to the MEI, or represent greater than 10% of the unabated PTE or represent greater than 25% of the abated dose.	Once per month when operating.

Sampling Requirements Smears of the exhaust vent when the system is operated at any time within a month.

Additional Requirements

Additional monitoring or sampling requirements established by this License will be listed in the Conditions and Limitations section, if applicable.

Operational Status The VES will be used to remove volatile organic compounds from soil gases and vapors from vents located in 218-W-3A

This Emission Unit has 1 active Notice(s) of Construction.

Project Title	Approval #	Date Approved	NOC_ID
Vapor Extraction System Operation (Replaces NOC 804)	AIR 16-1224	12/19/2016	1039

Conditions (state only enforceable: WAC 246-247-040(5), 060(5) if not specified)

- 1) The total abated emission limit for this Notice of Construction is limited to 1.50E-02 mrem/year to the Maximally Exposed Individual (WAC 246-247-040(5)).
- 2) This approval applies to those additional activities described below. No additional activities or variations on the approved activities that constitute a "modification" to the emission unit, as defined in WAC 246-247-030(16), may be conducted.

Transuranic waste retrieval involves the processes for removing and dispositioning buried suspect transuranic mixed low-level radioactive waste (hereafter called TRU waste) from Hanford Site burial trenches for storage or disposal at other approved locations. Dispositioning is the orderly administration and handling of waste (including contaminated soil) from the low level burial grounds to place it in approved storage or disposal status. The handling includes such actions as: packaging, labeling and tracking waste; venting, assaying, and staging waste; inspecting waste and waste staging areas; sampling/characterizing/designating waste; making arrangements for the transfer of waste; completing necessary paperwork; and performing radiological and/or industrial hygiene surveys.

See the following for a detailed description of specific controls/conditions for each EU associated with the

Transuranic Waste Retrieval Project:

- EU 455 Hanford Site-wide W-PORTEX 007
- EU 1440 200 Area Diffuse/ Fugitive; Operation of the Transuranic Waste Retrieval Project
- EU 755 Mobile Drum Venting System (Active Ventilation) (MDVS)
- EU 756 Mobile Drum Venting System (Passive Ventilation) (MDVS)
- EU 1181 Categorical Drum Venting System 2 (DVS2)
- EU 1322 Portable Enclosure System #1 (PES)
- EU 1326 Vapor Extraction System (VES)
- EU 1327 Next Generation Retrieval (NGR)

- 3) The PTE for this project as determined under WAC 246-247-030(21)(a-e) [as specified in the application] is $1.50E-02$ mrem/year. Approved are the associated potential release rates (Curies/year) of:

Am - 241 2.50E-03 Liquid/Particulate Solid
 Alpha release rate based on Am-241 + Progeny. It is recognized that other radionuclides may be present in very limited quantities.

Cs - 137 3.80E-02 Liquid/Particulate Solid
 Beta/Gamma release rate based on Cs-137 + Progeny. It is recognized that other radionuclides may be present in very limited quantities.

The radioactive isotopes identified for this emission unit are (no quantities specified):

- | | | | | |
|----------|----------|----------|----------|--------------|
| Am - 241 | Am - 243 | Cf - 252 | Cm - 244 | Cs - 134 |
| Cs - 137 | Eu - 152 | Eu - 154 | Pu - 238 | Pu - 239/240 |
| Pu - 241 | Sr - 90 | U - 234 | U - 235 | U - 236 |
| U - 238 | | | | |

The potential release rates described in this Condition were used to determine control technologies and monitoring requirements for this approval. DOE must notify the Department of a "modification" to the emission unit, as defined in WAC 246-247-030(16). DOE must notify the Department of any changes to a NESHAP major emission unit when a specific isotope is newly identified as contributing greater than 10% of the potential TEDE to the MEI, or greater than 25% of the TEDE to the MEI after controls. (WAC 246-247-110(9)) DOE must notify the Department of any changes to potential release rates as required by state or federal regulations including changes that would constitute a significant modification to the Air Operating Permit under WAC 173-401-725(4). Notice will be provided according to the particular regulation under which notification is required. If the applicable regulation(s) does not address manner and type of notification, DOE will provide the Department with advance written notice by letter or electronic mail but not solely by copies of documents.

- 4) RESTRICTION ON STARTUP

Prior to putting EU 1326, Vapor Extraction System into service, USDOE will provide WDOH with the technical specifications for the fan and filter housings. WDOH will need to approve and reissue the License for Operation of the Transuranic Waste Retrieval Project prior to startup.

- 5) RELEASE RATES - VES

It is assumed that there is a potential to have two degraded drums within the trench for the basis of the APQ, since only a portion of the trench is vented at any given time. Using a release fraction of $1E-03$ for particulates, the predicted release rate (unabated) for the VES without any emissions control equipment is $4.0E 02$ Ci/Yr. The predicted release rate (abated) with emissions control equipment is the same as unabated. The predicted release rates for the representative radionuclides Am-241+Progeny and Cs 137+Progeny are as follows:

Unabated PTE;	Am-241+Progeny	2.5E-03 Ci/yr	:	Cs-137+Progeny	3.8E-02 Ci/yr
Abated PTE;	Am-241+Progeny	2.5E-03 Ci/y	:	Cs-137+Progeny	3.8E 02 Ci/yr

(WAC 246-247-040(5) and WAC 246-247-060(5))

- 6) CONTROL TECHNOLOGY STANDARDS

The VES will contain HEPA-type filters, but no credit is taken for them in the system. This system will rely on the near facility monitors and, since there is no monitoring system in the VES, the listed standards are not applicable.

- 7) **CONTAMINATION CONTROL - Confirmatory Monitoring**
Periodic confirmatory monitoring will consist of periodic field surveys of swipes/smears taken at the exhaust point when the system is operated any time within a month, combined with the continuous monitoring provided by the 200 Area near facility ambient air monitoring network. (WAC 246-247-040(5) and WAC 246-247-060(5))

8) **PROCESS DESCRIPTION - VES**

This approval applies to these additional activities described below. No additional activities or variations on the approved activities that constitute a "modification" to the emission unit, as defined in WAC 246-247-030(16), may be conducted.

The VES will be used to remove volatile organic compounds (VOCs) from soil gases and vapors from vents located in 218-W-3A. A powered and filtered system will be attached to the VES risers and operated in batch mode. This process will consist of venting the vapor space and will not include venting during excavation or retrieval activities. The existing vent lines in the burial grounds will be connected to a powered ventilation system which will remove VOCs from the vapor space. The entire trench will not be vented as a unit, but the powered venting system will be positioned over a section of the trench and then moved further along, connecting to the nearest VES riser(s) as required per project direction.

Flexible hoses are connected from the vents to the VES. Vapor from the vents may be drawn through a demister and primary water separator (dropout tank) before it passes through a HEPA-type filter. The vapor stream leaving may then pass through a cooler before reaching the primary granular-activated carbon (GAC) canister. From the primary GAC canister the vapor line flows into the polishing GAC canister. The vapor stream leaving the polishing GAC canister is exhausted out of the VES stack. (WAC 246-247-040(5) and WAC 246-247-060(5))

9) **ABATEMENT TECHNOLOGY - Excavation and Retrieval of Containers**

It is recognized that other radionuclides may be present in very limited quantities. Encountering contamination is expected during excavation. The administrative control points set in this emission unit for contamination, as monitored by standard radiological field instrumentation, will be used to bound emissions based on current efficiencies of typical RadCon field contamination instruments.

The controls listed within this approval apply to TRU Waste Retrieval Project open air excavation and retrieval activities. (WAC 246-247-040(5) and WAC 246-247-060(5))

10) **ABATEMENT TECHNOLOGY - VES**

Operation of the Vapor Extraction System: A VES powered ventilation system operated for several years in the LLBG as a Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) activity associated with the Groundwater Project. No radionuclide particulate emissions were detected from the VES vents during this operation. However, based on engineering estimates and the operation of not venting the entire trench at once, but in a series of sections, it is assumed that the equivalent radionuclide contents of two degraded containers per vented section will provide the basis for the source of potential emissions. A HEPA type filter may be used, but no credit is taken for abatement. The annual average volumetric flow rate through this exhaust system is 4.7E-02 cubic meters/s. (WAC 246-247-040(5) and WAC 246-247-060(5))