



STATE OF WASHINGTON
DEPARTMENT OF ECOLOGY

3601 W. Washington • Yakima, Washington 98903-1164 • (509) 575-2800

June 6, 1994

Andrew den Hoed
Route 2 Box 2637
Grandview WA 98930-9691

Re: Emergency Drought Authorization under Application No. G4-31778

In accordance with the provisions of RCW 43.83B.405, on May 12, 1994 it was ordered and determined by the Director of the Department of Ecology that the Yakima River basin is under drought conditions. In accordance with the provisions of WAC 173-166-060, the Washington State Department of Ecology is under the terms of this Order, issuing an EMERGENCY DROUGHT PERMIT. This authorization is conditioned by the following provisions and limitations:

1. The initiation date of this EMERGENCY PERMIT is May 13, 1994.

This EMERGENCY PERMIT will terminate on or before December 1, 1994, unless sooner revoked by the Director of the Department of Ecology.

THIS AUTHORIZATION SHALL IN NO MANNER BE CONSTRUED TO GUARANTEE OR IMPLY THAT A FINAL (REGULAR) PERMIT WILL ISSUE FOR THE FUTURE USE OF THE FACILITY HEREIN AUTHORIZED.

2. This permit authorizes the construction of a well located in the NE $\frac{1}{4}$ SE $\frac{1}{4}$ of Section 1, T. 9 N., R. 23 E.W.M.
3. The following well construction requirements must be satisfied before water use as described below can be started:

The casing shall be set or placed (not driven) twenty (20) feet into the first solid, unfractured, nonporous, nonvesicular basalt flow of the Pomona Member of the Saddle Mountains Basalt Formation, and at least 240 feet below ground at the proposed site. The well annulus shall be pressure grouted using cement grout as a sealing agent from the bottom of the casing to land surface and the annulus shall be at least four (4) inches greater in diameter than the permanent casing. The well shall be restricted to a depth corresponding to the top of the Priest Rapids Member, estimated to occur at a 650 feet depth. The applicant is advised to avoid the sediment layer found approximately 50 feet above the Priest Rapids Member known as the Mabton interbed.

EMERGENCY PERMIT

Page 2

After completion of construction and clarification of the water by pumping or other means, the well shall be video scanned providing a clear, continuous image from the top of the well to the bottom. The video scan shall be provided to the Central Regional Office Water Resources Program of the Department of Ecology at 3601 W. Washington Ave., Yakima, WA. The Department is to be notified immediately of any well construction problems shown by the video scan.

For the purpose of making water level measurements, installation and maintenance of an access port as described in Ground Water Bulletin No. 1 is required. An air line and gage are also required. The air line shall be constructed of 1/4 inch minimum diameter galvanized steel pipe, or comparable material if pre-approved by the department. The air line shall be equipped with a standard tire (Schrader) valve. Distance from land surface to the bottom end of the air line shall be clearly posted at the well site, accurate to 0.5 feet or less. The air line, access port, and all well equipment shall be installed and maintained to provide access for measurement of water levels.

All water wells constructed within the state shall meet the minimum standards for construction and maintenance as provided under RCW 18.104 (Washington Water Well Construction Act of 1971) and Chapter 173-160 WAC (Minimum Standards for Construction and Maintenance of Water Wells).

4. A suitable flow meter approved by the Department of Ecology shall be installed and maintained in accordance with WAC 508-64-020 through WAC 508-64-040. (Installation, operation and maintenance requirements attached hereto.)

Whenever water is being diverted, bi-weekly (every two weeks) readings of the flow meter shall be recorded and maintained by the permittee. These readings shall be documented by time, date, withdrawal rate, and the person conducting the measurements. Copies of these records shall be submitted to the Department of Ecology at the end of the 1994 irrigation season.

5. The quantity of water to be withdrawn is limited to 450 gpm and 64 acre-feet per year. This is based upon the applicant's requested flow rate and an annual quantity of 0.8 acre-feet per acre.
6. Water is to be used for supplemental irrigation of 79.4 acres from April 1 to December 1, 1994. The place of use is described as follows:

E $\frac{1}{2}$ SE $\frac{1}{4}$ Section 1, T. 9 N., R. 23 E.W.M.; EXCEPT N 200 ft of S 430 ft of W 100 ft.


EMERGENCY PERMIT

Page 3

7. The irrigation water herein authorized to be withdrawn is supplemental to water made available under primary rights by the Roza Irrigation District. The only water herein permitted for withdrawal is water necessary to alleviate hardships and reduce burdens on water users arising from drought conditions. This amount shall not exceed 0.8 acre-feet per year per acre.
8. Withdrawal of water under this right may be limited or otherwise regulated in favor of senior rights.
9. Construction of the well under this permit must begin by October 1, 1994. No new well construction shall be allowed after this date. Construction of the well shall be completed no later than October 15, 1994.

You have the right to obtain review of this order. Request for review must be made, within thirty (30) days of receipt of this order, to the Washington Pollution Control Hearings Board, PO Box 40903, Olympia, Washington 98504-0903. Concurrently, a copy of the request must be sent to the Department of Ecology, PO Box 47600, Olympia, Washington 98504-7600. These procedures are consistent with the provisions of Chapter 43.21B RCW and the rules and regulations adopted thereunder.

Sincerely,



Doug Clausing
Section Manager
Water Resources Program

DC:TR:gh
940617.wr4

Enclosures: Flow Measurement Record
Flow Meter Requirements
Ground Water Bulletin No. 1
Water Well Report Form

cc: Yakama Indian Nation
Dale Bambrick
Wendell Hannigan